US 20080252607A1

(19) **United States**

(12) **Patent Application Publication**

De Jong et al.

(10) **Pub. No.: US 2008/0252607 A1**

(43) **Pub. Date: Oct. 16, 2008**

(54) **IMAGE DISPLAY THAT MOVES PHYSICAL OBJECTS AND CAUSES TACTILE SENSATION**

(75) Inventors: **Nicolas De Jong**, Veldhoven (NL); **Elmo Marcus Attila Diederiks**, Eindhoven (NL); **Murray Fulton Gillies**, Eindhoven (NL); **Jurgen Jean Louis Hoppenbrouwers**, Eindhoven (NL); **Johannes Henricus Maria Korst**, Eindhoven (NL); **Thomas Casper Kraan**, Eindhoven (NL); **Rogier Winters**, Weert (NL)

Correspondence Address:
PHILIPS INTELLECTUAL PROPERTY & STANDARDS
P.O. BOX 3001
BRIARCLIFF MANOR, NY 10510 (US)

(73) Assignee: **KONINKLIJKE PHILIPS ELECTRONICS, N.V.**, EINDHOVEN (NL)

(21) Appl. No.: **11/719,996**

(22) PCT Filed: **Nov. 30, 2005**

(86) PCT No.: **PCT/IB2005/053990**

§ 371 (c)(1),
(2), (4) Date: **Mar. 7, 2008**

Related U.S. Application Data

(60) Provisional application No. 60/632,133, filed on Dec. 1, 2004.

Publication Classification

(51) **Int. Cl.**
G09G 5/00 (2006.01)

(52) **U.S. Cl.** **345/173**

(57) **ABSTRACT**

An image display including a touch-sensitive display, that creates tactile sensation and movement of an object (**3-2**) along its surface is provided. Actuators including conductive rods (**4-111**, **4-112**) attached together may be used, such that each rod of the actuator (**4-11**) may increase or decrease in size when current is applied to that rod to cause the actuator to bend toward a specified direction. Also, an image display that includes ball bearings (**1-10**) whose rotation is controlled by driving magnets (**1-21**, **1-22**) to cause an object to move is provided. Further, air holes (**3-11**) tilted in various directions to control object movement by air pressure may be provided. Moreover, rods (**3-10**) may be moved up or down as activated by driving magnets (**2-20**). The actuators, rods, ball bearing assemblies, or holes may provide touch sensitivity for the image display.